ACCSOON

Professional Photo Equipment

TOPRIG S40

Motorized Video Slider

Cable & Smooth

Speed Control 0.1cm/s-5cm/s

Brushless Motor

Max Load of 4kg/8.8lbs

AB Points Setting

Time Lapse

App Control

Ultra Silent

Stability is the key

Suitable for either telephoto or macro probe lenses

Speed Control Made Simple

An intuitive control knob that allows speed control from 0.1cm/s to 5cm/s

0.1cm/s - 5cm/s

Great Power

Various models of micro-single and light movie cameras can be supported at maximum bear load 2.2kg vertically and 4kg horizontally.

2.5KG-4KG

Built-in Panel Button Control

Noise Free

TOPRIG S40/S60 is equipped with a high quality brushless motor which features powerful yet precise control and operates without noise.

Smooth Start/Stop

Smooth Start/Stop to ensure a complete stable video footage



TOPRIG S40/S60 adopts a S-curve soft start/stop mechanism for a stable and smooth shoot.

NP-F Battery or DC Power

Low power consumption & longer working hours

TOPRIG S40/S60 can run at least 60 hours horizontally with a single NP-F550 battery (3200MAH)

Multi-angle movement support

New guide wheel tensioning design ensures continuous work and meets a variety of shooting patterns



Light Compact Portable



Specifications

S40

Rated Voltage	7.4-19.8V
Max Horizontal Load	4kg
Max Vertical Load	2.2kg
Max Operating Speed	5cm/s
Stationary Object Tracking Panoramic Angle	50°
Max Travel Distance	420mm
Power Supply	DC 9-19.8V NP-F Battery
Power Consumption	0.5w
Dimensions	410mm x 108mm x 71.3mm
Weight	1.4kg

S60

Rated Voltage	7.4-19.8V
Max Horizontal Load	4kg
Max Vertical Load	2.2kg
Max Operating Speed	5cm/s
Stationary Object Tracking Panoramic Angle	50°
Max Travel Distance	420mm
Power Supply	DC 9-19.8V NP-F Battery
Power Consumption	0.5w
Dimensions	410mm x 108mm x 71.3mm
Weight	1.9kg

In The BOX

S40

TOPRIG S40	×1
Spare Belt	×1
User Manual	×1
Certificate of Quality	×1

S60

TOPRIG S60	×1
Spare Belt	×1
User Manual	×1
Certificate of Quality	×1
Soft Case	×1