



Antenna Pro-5000-5G, 11dBi for GSM/2G/3G/4G/5G

A log-periodic antenna for the frequency bands 698-960/1710-2700/3300-3600/4800-5000 MHz. This antenna is specially developed for our Scandinavian networks and now also for 5G. The design consists of an encapsulated yagi antenna with a smart mount that allows the antenna to be angled to optimize reception.

Ref.	650503
EAN13	8424450236819

Other features

Colour	White
---------------	-------

Packaging info

Box	1 Units
------------	---------

Physical data

Net weight	1,162.00 g
Gross weight	1,380.00 g
Width	445.00 mm
Height	210.00 mm
Depth	70.00 mm
Main product weight	1,162.00 g

Highlights

- Two Pro-5000-5G can be used for MIMO function
- The antenna can be mounted both vertically and horizontally

- 7.5 meter white low-loss cable (type LMR200)
- SMA connector (male)
- Can be mounted on pipes 30-53 mm

Technical specifications : Ref. 650503

Telephony bands		2G	3G	4G	5G
Frequency range	MHz	698 ... 960	1710 ... 2700	3300 ... 3800	4800 ... 5000
Gain	dBi	10 ... 11			
Input impedance	Ω	50			
Polarisation		Horizontal/Vertical			
Horizontal beamwidth	°	60			
Vertical beamwidth	°	50			
F/B ratio	dB	> 21			
Max. power	W	100			
Number of connectors		1			
Connector type		SMA Male			
Cable length	m	7			
Grounding		Yes			
Mast diameter	mm	30 ... 53			
Operating temperature	°C	-40 ... 60			