



2-WAY SPLITTER LOW PIM ART.NR 586842

3-WAY SPLITTER LOW PIM ART.NR 586843

4-WAY SPLITTER LOW PIM ART.NR 586857

| | | | |
|---------------------|-----------------------------------|-----------------|--------------------|
| Art.nr | 586842 | 586843 | 586857 |
| Frequency Range | 698-4200 MHz | | |
| Band Support | 1/3/7/8/20/28L/28U/40/n48/n78/n77 | | |
| Input Port Number | 1 | | |
| Output Port Number | 2 | 3 | 4 |
| Connectors | 4.3-10-Female | | |
| Power Divider Class | Wilkinson | | |
| Insertion Loss (dB) | ≤1.0 | ≤1.5 | ≤1.5 |
| Split Loss (dB) | 3.0 | 4.8 | 6.0 |
| Port Isolation (dB) | ≥22 | ≥20 | ≥18 |
| VSWR | ≤1.3 | | |
| 3 rd PIM | ≤-153dBc@2*43dBm | | |
| Input Impedance | 50Ω | | |
| Average Power | 50W (46.99dBm) | | |
| Color | Black | | |
| Operating Temp. | -30 °C to +70 °C | | |
| IP Rating | IP65 | | |
| Dimensions | 120 x 60 x 29mm | 225 x 45 x 29mm | 142.5 x 121 x 29mm |
| RoHS | Compliant | | |

MECHANICAL DRAWING

