

F-compression connector CX3 5.0 QM short, 50 pcs. box

Art. Number 360949



F-56-CX3 5.0 QM

F-compression connector quick mount for very easy mounting on the coax cables.

- Waterproof
- Class A+
- Fast mounting, no braid fold back
- Perfect for hard cables with PE-jacket

Technical Specifications

ORDER INFORMATION

EAN Number 5702663609495

SHIELDING

Shielding @ 30-1000 MHz | dB > 120 dB

Shielding @ 1000-2000 MHz | dB > 110 dB

Shielding @ 2000-3000 MHz | dB > 110 dB

TRANSFER IMPEDANCE

Transfer Impedance @ 5-30 MHz | mΩ/m < 2.5 mΩ/m

CHARACTERISTICS

Cable type 5 mm

Tool 153603, 153630

FREQUENCY RANGE

Frequency range | MHz 0.3-3000 MHz

LOSS

Insertion loss (typ.) | dB -0.01 @ 860-1000 MHz dB

RETURN LOSS

Technical Specifications

Return Loss dB	-33.3 @ 860-1000 MHz dB
------------------	-------------------------

ELECTRICAL

Impedance Ω	75 Ω
----------------------	-------------

OPERATIONAL

Screening Efficiency	EN50117 (Class A++)
----------------------	---------------------

Temperature - operating °C	-40...100 °C
------------------------------	--------------

MECHANICAL

Plating	NiTin 6
---------	---------

Packing QTY	50
-------------	----

Packaging Height m	0.001 m
----------------------	---------

Packaging Width m	0.002 m
---------------------	---------

Packaging Depth m	0.001 m
---------------------	---------

Packaging Volume m3	0.000 m3
-----------------------	----------

Net Weight kg	0.010 kg
-----------------	----------

Tara Weight kg	0.000 kg
------------------	----------

Total Weight kg	0.010 kg
-------------------	----------