



2-WAY SPLITTER ART.NR 586840

Frequency Range (MHz)	698-4000
Band Support	1/3/7/8/20/28L/28U/40/n48/n78
Input Port Number	1
Output Port Number	2
Connectors	N-Female
Power Divider Class	Wilkinson
Insertion Loss (dB)	≤ 0.5
Splitt Loss (dB)	3.0
Port Isolation (dB)	≥ 20
VSWR	≤ 1.3
Input Impedance	50 Ω
Average Power	50W (46.99dBm)
Color	Black
Operating Temperature	-35 °C to +65 °C
Relative Humidity	5% to 95%
IP Rating	Indoor use only
Dimensions	88 x 60 x 20.5mm
RoHS	Compliant

3-WAY SPLITTER ART.NR 586841

Frequency Range (MHz)	698-4000
Band Support	1/3/7/8/20/28L/28U/40/n48/n78
Input Port Number	1
Output Port Number	3
Connectors	N-Female
Power Divider Class	Wilkinson
Insertion Loss (dB)	≤ 1.2
Splitt Loss (dB)	4.8
Port Isolation (dB)	≥ 18
VSWR	≤ 1.3
Input Impedance	50 Ω
Average Power	50W (46.99dBm)
Color	Black
Operating Temperature	-35 °C to +65 °C
Relative Humidity	5% to 95%
IP Rating	Indoor use only
Dimensions	94.5 x 77 x 23mm
RoHS	Compliant

MECHANICAL DRAWING

