


2-WAY SPLITTER LOW PIM ART.NR 586842

Frequency Range	698-4200 MHz
Band Support	1/3/7/8/20/28L/28U/40/n48/n78/n77
Input Port Number	1
Output Port Number	3
Connectors	4.3-10-Female
Power Divider Class	Wilkinson
Insertion Loss (dB)	≤1.0
Split Loss (dB)	3.0
Port Isolation (dB)	≥22
VSWR	≤1.3
3 rd PIM	≤-153dBc@2*43dBm
Input Impedance	50Ω
Average Power	50W (46.99dBm)
Color	Black
Operating Temp.	-30 °C to +70 °C
IP Rating	IP65
Dimensions	120 x 60 x 29mm
RoHS	Compliant

3-WAY SPLITTER LOW PIM ART.NR 586843

Frequency Range	698-4200 MHz
Band Support	1/3/7/8/20/28L/28U/40/n48/n78/n77
Input Port Number	1
Output Port Number	3
Connectors	4.3-10-Female
Power Divider Class	Wilkinson
Insertion Loss (dB)	≤1.5
Split Loss (dB)	4.8
Port Isolation (dB)	≥20
VSWR	≤1.3
3 rd PIM	≤-153dBc@2*43dBm
Input Impedance	50Ω
Average Power	50W (46.99dBm)
Color	Black
Operating Temp.	-30 °C to +70 °C
IP Rating	IP65
Dimensions	225 x 45 x 29mm
RoHS	Compliant

MECHANICAL DRAWING
